

CHR® SGK5-05

Para-Aramid Wiring Harness Tape

CHR SGK5-05 is manufactured from extra-strength, para-aramid (phenyleneterephthalamide) fiber cloth, impregnated with a dispersion of anti-static PTFE (polytetrafluoroethylene). This high performance coated fabric then has a layer of high temperature silicone adhesive applied to one side. The black pigmentation provides anti-static performance and protection from UV damage, to which para-aramid fiber cloth is susceptible. Resistivity of this version is less than 10^6 ohms/in².

Features/Benefits

Anti-static PTFE coated para-aramid cloth provides strength, flexibility, slip, chemical resistance and UV stabilization in harsh environments where protection against abrasion commonly wears out standard fiberglass harness wraps. Low coefficient of friction PTFE adds another dimension to harness wrapping by providing a measure of “lubricity.” Additionally, PTFE extends high temperature resistance to plain para-aramid (phenyleneterephthalamide) fiber cloth.

Availability

CHR SGK5-05 is available only in 0.127 mm (5.0 mil) thicknesses. Factory stock as Master Rolls are 33 m long by 1,219 mm (36 yd × 48 in) wide. Slit rolls are available from 12 mm (0.5 in) wide. **CHR** SGK5-05 is available with or without a liner. The lined version is referenced as **CHR** SGK5-05R.

Applications

CHR SGK5-05 is specifically designed to resist abrasion, and provide added strength in high temperature cable wrapping applications where standard fiberglass cloth do not provide adequate chemical resistance and/or low friction release.



CHR SGK5-05 Properties

Performance tests are run using standard test procedures.

The values presented are typical values and should not be used for specification purposes.

Product Number	SGK5-05
Backing Material	PTFE Coated Para-Aramid Woven Fabric
Adhesive Type	Super Stick Silicone
Total Thickness mm (mil)	0.178 (7.0)
Backing Thickness mm (mil)	0.127 (5.0)
Adhesive Thickness mm (mil)	0.051 (2.0)
Adhesion to Steel N/cm (oz/in)	2.7 (25)
Tensile Strength N/cm (lb/in) warp × weft	350 × 350 (200 × 200)
Elongation at Break (%)	3
Resistivity (ohms/in ²)	<10 ⁶
Operating Temperature °C (°F)	-73 to +260 (-100 to +500)
Colour	Black



Saint-Gobain Tape Solutions

North America | South America | Europe | Asia

For a full list of locations, please visit
[tapesolutions.saint-gobain.com/contact-us](https://www.tapesolutions.saint-gobain.com/contact-us)

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1098 | © Saint-Gobain May 2020 | **CHR** and **CHRTape** are trademarks of Saint-Gobain.